

[54] REFLECTANCE MEASURING APPARATUS INCLUDING A CYLINDER-SHAPED LIGHT CONDUCTING DEVICE BETWEEN THE MEASURING APERTURE AND THE SPECIMEN

[75] Inventor: Hermann Gerlinger, Aalen, Fed. Rep. of Germany

[73] Assignee: Carl-Zeiss-Stiftung, Heidenheim, Fed. Rep. of Germany

[21] Appl. No.: 358,661

[22] Filed: May 30, 1989

[30] Foreign Application Priority Data

Jun. 3, 1988 [DE] Fed. Rep. of Germany ..... 3818815

[51] Int. Cl.<sup>4</sup> ..... G01T 1/00

[52] U.S. Cl. .... 250/228; 356/236

[58] Field of Search ..... 250/228, 237 R; 356/236, 445, 446, 447, 448; 362/16, 297, 347, 350, 356, 458, 809

[56] References Cited

### U.S. PATENT DOCUMENTS

2,358,020	8/1940	Miller .....	88/14
4,453,180	6/1984	Juergensen .....	250/228
4,523,853	6/1985	Rosenblatt et al. ....	356/446
4,651,262	3/1987	Piironen .....	262/350

### OTHER PUBLICATIONS

J. Phys. E: Sci. Instrum., vol. 18, 1985, H. H. Schlemmer and M. Mächler "Diode Array Spectrometer: an Optimised Design" pp. 914 to 919.

Primary Examiner—David C. Nelms

Assistant Examiner—William L. Oen

Attorney, Agent, or Firm—Walter Ottesen

### [57] ABSTRACT

The invention is directed to a reflectance measuring apparatus having a predetermined aperture for the receiving optic. A light-conducting device arranged between the measuring aperture and the specimen enlarges the effective measuring surface of the latter so that even specimens having a large surface structure can be measured without difficulty.

15 Claims, 2 Drawing Sheets

